

U-19



A 19" display with the perfect balance of function, form and frugality befitting the most efficient and best-designed multi-user environments.

For the consummate display professional the AG Neovo U-19 is the optimal combination of screen real-estate, features excellence and power-saving economy. A 19" screen displays crisp, bright video, yet saves up to half the power used by standard monitors. A smart, sleek design ensures not only perfect fit, but also ease of use with touch-sensor controls, built-in speakers, headphone jack and USB port. And with a long-life panel protected by NeoV™ Optical Glass, the U-19 won't just work like new for years to come, but also look it too.

- > NeoV™ Optical Glass
- > Contemporary & professional design
- > 1280 x 1024 resolution, 1000:1 contrast ratio and 3ms response
- > Eco-friendly: Slash CO₂ emissions up to 50%; Recyclable materials and green design
- > Energy efficient: Cut power bills up to 50%; Zero-watt consumption with EcoSwitch
- > Built-in headphone jack and stereo speakers
- > Wear-resistant touch sensor controls
- > Easy-access USB port (pass through)
- > New intuitive OSD with settings lock
- > Dual PC inputs: VGA and DVI
- > Kensington® security socket
- > VESA standard wall mount



NeoV™ Optical Glass - The most trusted hard glass protection available. Only on AG Neovo displays

U-19

Specifications

U-19

| | | |
|-----------------------------|--|--|
| Panel | Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Viewing Angle (H/V) Display Colour Response Time | LED-backlit TFT LCD 19.0" (482 mm) SXGA 1280 x 1024 0.294 mm 250 cd/m ² (Typical) 1000:1 (Typical) 170°/160° (Typical) 16.7M 3 ms (GTG) |
| Frequency (H/V) | | H: 24 kHz - 81 kHz V: 56 Hz - 75 Hz |
| Input | Analogue Digital | 15-Pin D-Sub 24-pin DVI-D |
| Audio | Audio In Audio Out Speaker | 3.5 mm Audio Line-in 3.5 mm Headphone Jack 1W x 2 |
| Power | Power Supply Power Requirements Consumption | Internal AC 100 - 240 V, 50 - 60 Hz < 17W (On) < 0.5W (Stand-by) < 0.5W (Off) = 0W (EcoSwitch Off) |
| NeoV™ Optical Glass | Thickness Reflection Rate Transmission Rate Coating Hardness | 3.0 mm (0.12") < 1% > 96% > 9H |
| Plug & Play | VESA | DDC 2B, DDC/CI |
| Operating Conditions | Temperature Humidity | 0 °C ~ 40 °C 10% ~ 90% |
| Storage Conditions | Temperature Humidity | -20 °C ~ 60 °C 5% ~ 95% |
| Mounting | VESA FPMPMI | Yes (100 x 100mm) |
| Tilt | Tilt | +0° ~ +20° |
| Dimensions | Product (W x H x D) Packaging (W x H x D) | 440 x 417 x 174 mm (17.3" x 16.4" x 6.8") 538 x 520 x 163 mm (21.2" x 20.5" x 6.4") |
| Weight | Product Packaged | 5.7 kg (12.6 lbs) 7.0 kg (15.4 lbs) |
| Regulation Approval | Certifications & Compliance | CB, FCC, CE, BSMI, GOST-R, WEEE, Energy Star, RoHS, REACH |
| Accessories | Supplied | CD ROM (user manual and drivers), audio cable, power cord, 15-Pin D-Sub cable |



Side-mount headphone jack, USB port and built-in stereo speakers for multimedia convenience



Durable, long-lasting touch sensor controls won't wear out like mechanical buttons



NeoV™ Optical Glass protects against scratches, impacts and other physical damage



Slash power bills and CO₂ emissions by up to 50% (67% versus CRTs); EcoSwitch cuts power usage to zero when off

